

LASER RECEIVERS

AUSTRALIA'S BEST SELECTION



Model:
The Laserometer Receiver
(mm Digital Readout)

Features:

- Accuracy: 0.5, 1.0, 2.0, 5.0 & 10.0mm
- Display: LCD & LED mm readout. (21 CH)
- Display: Front & Back & Backlit
- Range Dia: 950m
- Volume Settings: Four
- Battery: 60 hrs continuous
- Reception Window: 127mm
- Auto Off: 30 mins
- Low Battery Indicator: YES
- IP67: Water & dust Proof.
- LED 2 colour, 3 channel, perfect for low light conditions
- 21 Segment Channels
- Built in level vial
- Strobe rejection
- Two position rod clamp
- Reversible clamp jaws, square and round
- Warranty 3 years

Made in USA

Model: Storm or HL-700



Model:
Acceptor 2 Receiver mm

Features:

- Accuracy: 1mm, 4mm & 6mm
- Display: LCD & LED mm readout (9 CH)
- Display: Front & Back
- Range Dia: 550m
- Volume Settings: Three
- Battery: 120 hrs continuous
- Reception Window: 50mm
- Auto Off: 15 mins
- Low Battery Indicator: YES
- IP67: Water & dust Proof.
- Magnets: Top
- Warranty: 3 Years
- Made in Germany



Model:
Acceptor MAXX
(mm Digital Readout)

Features:

- Accuracy: 1mm, 2mm, 4mm and 8mm
- Display: LCD and LED Front, Rear & Sides
- Display: Illuminated Displays. mm Readout
- Range: 900m Dia
- Volume Settings: 3 plus mute.
- Battery: 60 hrs
- Reception Window: 120mm
- Auto Off: 15minutes.
- Low Battery Indicator: Show on Display
- IP67: Protection Water & Dust
- Operating Temp: -20C to +60C
- Made in Germany



AMA Machine Detector 360

(Plumb Indicator & 360Deg Reception)

Features:

- Accuracy: 4mm, 8mm & 12mm
- Display: LED's Up, Down, On Grade
- Display: High Intensity in sunlight
- Range Dia: 1000m
- Volume Settings: Three
- Battery: 40 hrs continuous = 1 week.
- Reception Window: 200mm
- Auto Off: 5mins, **Shake to Wake**
- Low Battery Indicator: YES
- IP65: Water & dust resistance.
- Magnets: 2 x Permanent Round Head
- Warranty: 2 Years
- Made in Sweden

Model LE360

