



Nedo Laser Receiver ACCEPTOR^{pro}



Features:

- Extremely robust laser receiver
- Large detector field with 70 mm length
- Large LC display on front and back
- Bright LED display
- Adjustable volume
- Display of remaining battery power
- Easy to handle
- Rod clamp for laser receiver

Ref.-No. 430 372

Technical data:

- Accuracy: switchable, ± 0.5 mm, ± 1.0 mm, ± 2.0 mm, ± 4.0 mm
- Length of detector field: 70 mm
- Working range: \varnothing 700 m (depends on laser)
- Protection class IP 66
- Operating temperature: -20°C to $+50^{\circ}\text{C}$
- Power supply: 3 x 1.5 V batteries (AA) or rechargeable batteries (NiMH)
- Operation duration: approx. 100 h

Nedo Laser Receiver COMMANDER²



Features:

- Laser receiver with integrated radio remote control
- Large LC display on front and back
- Plain-language LCD display showing all the data of the PRIMUS² displays
- Bright LED display
- Adjustable volume
- Large detector field with 70 mm length
- Display of remaining battery power
- Rod clamp for laser receiver

Ref.-No. 430 371 COMMANDER² H2N

Ref.-No. 430 374 COMMANDER² H2N+

Technical data:

- Accuracy: switchable, ± 0.5 mm, ± 1.0 mm, ± 2.0 mm, ± 4.0 mm
- Length of detector field: 70 mm
- Working range: \varnothing 700 m (depends on laser)
- Protection class IP 66
- Operating temperature: -20°C to $+50^{\circ}\text{C}$
- Power supply: 3 x 1.5 V batteries (AA) or rechargeable batteries (NiMH)
- Operation duration: approx. 100 h



Video ACCEPTOR²

The multifunctional rod clamp allows the laser receiver to be securely fastened to rods and batter boards without any additional accessories.



Nedo Laser Receiver ACCEPTOR²

Extremely robust laser receiver with multifunctional rod clamp with patented quick clamp and batter board function.



Features:

- Extremely robust laser receiver
- Large detector field: 50 mm
- Large LC display on front and back
- Bright LED display
- Adjustable volume
- Display of remaining battery power
- Strong magnets for fixing to steel girders
- Protected against powerful jet water to IP 67
- Two accuracy modes: coarse and fine
- Bubble for easy alignment
- Multifunctional rod clamp with patented quick clamp and batter board function
- Vertical attachment for around-the corner applications
- Stop blade for wood measuring aids

Ref.-No. 430 333



Technical data:

- Accuracy: switchable, ± 4.0 mm/ ± 1.0 mm
- Working range: \varnothing 550 m (depends on laser)
- Protection class IP 67
- Power supply: 2 x 1.5 V (AA)
- Operation duration: approx. 120 h (batteries)
approx. 100 h (rechargeable batteries)